

Smart Wireless Solar PTZ Camera

Specification:

Product Image:

- * Wireless Solar PTZ camera
- * Low power consumption, 6-7 Month's Standby time
- * HD 3MP Video Quality, support night vision.
- * PIR motion sensor with 90° detection angle , accurate motion detection
- * Support 2.4G WiFi, Free P2P cloud service, push alarm to mobile via APP.
- * Support 2-way audio communication, support TF-card Storage

Innotronik



Specification

| Model NO. | ICS-PT50 | |
|-------------|----------------------|--|
| Video | Sensor | 1/2.8"CMOS Q03 |
| | Chipset | XM650 |
| Video | Resolution | HD 3MP |
| | Frame rate | 25fps |
| | Resolution | 2048*1536 |
| | Lens | 90°wide-angle |
| | Night vision | 4pcs Infra-Red+ 4pcs white light leds, IR Range: 50M |
| Audio | Type | 2-way audio with noise-cancellation |
| | Hardware | One Microphone and one speaker |
| Storage | Cloud | Support Cloud storgage |
| | TF Card | TF card max 128GB |
| Network | WiFi (2.4GHz) | IEEE 802.11 b/g/n |
| | Stream | Dual stream |
| | Network Protocol | Support TCP/IP, ONVIF, private cloud storage, etc. |
| | transmission mode | P2P,Smart Cloud Sever |
| PTZ | Pan | 355° |
| | Tilt | 90° |
| | Digital Zoom | 4X Digital Zoom |
| App | Download | ios in App Store, Android in Google Play |
| | Name | XMEYE/ICSEE |
| | Device Wakeup | Within 600ms |
| | Notification | Push notification within 1 second |
| Solar Panel | Power | 3W |
| | Apex voltage | DC 5V |
| | Solar panel Size | 238*172*16.5mm |
| | Standby time | 6-7 months |
| Others | Power | DC5V/Solar Panel (Optional) |
| | Battery | 12000mA |
| | Material | ABS |
| | Temperature&Humidity | -20°C ~ 55. C&10-95% RH |
| | Weatherproof | IP66 |
| | Size | 156*105*170mm (L*W*H) |