

Model	REP3000-121	REP3000-241	REP3000-481	REP3000-122	REP3000-242	REP3000-482	
Rated power	3000W						
Peak power	6000W						
Input voltage	DC12V	DC24V	DC48V	DC12V	DC24V	DC48V	
Output voltage	100VAC or 110VAC or 120VAC±5%			220VAC or 230VAC or 240VAC±5%			
Unload current less than	0.77	0.51	0.35	0.77	0.51	0.35	
Output frequency	50Hz±0.5Hz or 60Hz±0.5Hz						
Output waveform	Pure Sine Wave						
Waveform distortion	THD < 3%(Linear load)						
USB port	5V 1A						
Max.efficiency	90%	92%	95%	90%	92%	95%	
Input voltage range	10-15.5V	20-31V	40-61V	10-15.5V	20-31V	40-61V	
Low voltage alarm	10.5±0.5V	21±0.5V	42±1V	10.5±0.5V	21±0.5V	42±1V	
Low voltage protection	10±0.5V	20±0.5V	40±15V	10±0.5V	20±0.5V	40±15V	
Over voltage protection	15.5±0.5V	31±0.5V	61±1V	15.5±0.5V	31±0.5V	61±1V	
Low voltage recover	13±0.5V	24±0.5V	48±1V	13±0.5V	24±0.5V	48±1V	
Over voltage recover	14.8V±0.5V	29.5V±0.5V	59V±1V	14.8V±0.5V	29.5V±0.5V	59V±1V	
Protection function	Low voltage		Alarm at first, voltage continuously reduce. LED Red light on & shut sown.				
	Over voltage		LED Red light on, shut down				
	Over load		LED Red light on, shut down				
	Over temperature		Alarm at first, tempurature continuously rise.LED Red light on & shut sown				
	Short circuit		LED Red light on				
	Input reverse polarity		Fuse burn-out				
Working temperature	-10° - +50°						
Storage temperature	-30° - +70°						
Dimension(mm)	395x180x130mm						
Packing(mm)	500x280x220mm						
Net./gross weight(g)	6210/8000g						
QTY/Ctn	2 Pcs						
Meas./Ctn(mm)	520x200x270mm						
Gross weight/Ctn(g)	16000g						
Warranty	2 years						
Configuration	Standard						
Cooling method	Intelligent air cooling						