

ROG RAPTURE JT-HXIJOOO PRU



Overwhelming powerful WiFi 6 Tri-band AX11000 gigabit WiFi gaming router

- High-Efficiency WiFi 6 Ultrafast WiFi 6 tri-band boosts speeds up to 11,000 Mbps, with 160 MHz channels for better efficiency and throughput.
- Expanded Coverage Exclusive ASUS RangeBoost Plus improves signal range and overall coverage.
- Flexible Networking Ports One 2.5 G port and one 10 G port can be configured for either WAN or LAN operation.
- Extreme Quad-Core CPU Power High-performance WiFi chipsets and 64-bit 2.0 GHz quad-core CPU take wireless signal processing to the next level.
- Triple-Level Game Acceleration Online gaming gets network prioritization every step of the way, from PC to game server.
- Expanded UNII4 Spectrum Additional high-power 160 MHz channel in 5 GHz increases backhaul capacity of the Mesh network.

Warp-speed WiFi 6

ROG Rapture GT-AX11000 Pro tri-band WiFi 6 router uses the latest technology to give you combined wireless speeds of up to 11000Mbps – which is 2.53X faster than WiFi 5. WiFi 6 also gives your network more capacity, with improved range and longer battery life for your devices.* * To benefit from WiFi 6 features, the WiFi client needs to be WiFi 6 capable

Capacity up to

Faster 2.5x WiFi 6 (802.11ax) GT-AX11000 Pro

11000 Mbps

4266 Mbps

WiFi 5 (802.11ac)



Accelerate Your Game - From Device to Server

ROG Rapture GT-AX11000 Pro provides triple-level game acceleration to boost game traffic every step of the way.





Expanded UNII4 spectrum

GT-AX11000 Pro has been upgraded to support an expanded UNII4 spectrum featuring a high-powered 160MHz channel on the 5GHz band. This increases the backhaul capacity of the mesh and improves signal efficiency for roaming and coverage.

5GHz 20 MHz 40 MHz 80 MHz 160 MHz NEW Three 160MHz channels

Flexible Network Ports Functions

GT-AX11000 Pro comes with one 2.5G port and a 10G port that work both WAN and LAN. It not only provides additional bandwidth for connected devices but also increases ports' flexibility for heavy duty network usage.




Connectivity









Control Your Network Anywhere.

ASUS Router App

ASUS Router App allowing you to setup your router, manage network traffic, diagnose connection issues and even update firmware, all without needing to boot up a PC.











What's Inside the Box

- ROG Rapture GT-AX11000 Pro Tri-band Gaming Router
- RJ-45 cable
- Power adapter
- Warranty card
- Quick start guide

Specifications

- Wireless Type: 802.11 ax(5GHz/2.4GHz)/ac/n/g/a/b
- Wireless Speed: 2.4GHz up to 1148 Mbps / 5GHz-1 up to 4804Mbps / 5GHz-2 up to 4804Mbps
- Wired Connectivity: 4 x LAN ports, 1 x 2.5G WAN port,
- 1 x 10G WAN/LAN port
- USB Ports: 1 x USB 3.2 Gen 1(USB 3.0) port, 1 x USB 2.0 port
- Warranty: 2 years (varies by regions)



Scan to check full specs



PECIFICATION OG RAPTURE GT-AX11000 Pro AX11000 ultimate AX performance Product Segment Coverage Very Large homes 802.11ax (2.4GHz) : up to 1148 Mbps 802.11ax (5GHz - 1): up to 4804 Mbps Data Rate 802.11ax (5GHz - 2): up to 4804 Mbps External antenna x 8 (Undetachable antenna) Antenna 2.4 GHz: 4 x 4 Transmit/Receive 5 GHz - 1:4 x 4 5 GHz - 2:4 x 4 **Processor** 2.0 GHz quad-core processor 256 MB Flash Memory 1 GB DDR4 RAM OFDMA (Orthogonal Frequency Division Multiple Access) Beamforming: standard-based and universal Wi-Fi Technology 1024-QAM high data rate 20/40/80/160 MHz bandwidth 2.4 GHz / 5 GHz - 1 / 5 GHz - 2 Operating Frequency WPA3-Personal, WPA2-Personal, WPA-Personal, WPA-Enterprise, Encryption **WPS** support Firewall: SPI intrusion detection, DoS protection Firewall & Access Control Access control: Parental control, Network service filter, URL filter, Port filter UPnP, IGMP v1/v2/v3, DNS Proxy, DHCP, NTP Client, DDNS, Management Port Trigger, Port Forwarding, DMZ, System Event Log **IPSec Pass-Through** PPTP Pass-Through L2TP Pass-Through **IPSec server** VPN Support PPTP server OpenVPN server **PPTP** client L2TP client OpenVPN client Internet connection type: Automatic IP, Static IP, PPPoE(MPPE supported), PPTP, L2TP WAN Connection Type Utilities Router setup wizard; Firmware restoration; Device discovary; printer setup utility RJ45 for 2.5G BaseT for WAN x 1, RJ45 for Gigabits BaseT for LAN x 4, RJ45 for 10G BaseT for WAN/LAN x 1 **Ports** USB 3.2 Gen 1 x 1, USB 2.0 x 1



	Router app
	Link Aggregation - 802.3ad
	MU-MIMO
	Traffic Analyzer
	Adaptive QoS
	AiProtection Pro
	Parental Control
	Guest Network: 2.4 GHz x 3, 5 GHz x 3, 6 GHz x 3
	VPN server : PPTP Server, OpenVPN Server, IPSec server
	VPN client : PPTP client, L2TP client, OpenVPN client
	NAT Pass-Through :PPTP Pass-Through, L2TP Pass-Through, IPSec Pass-Through, RTSP Pass-
	Through, H.323 Pass-Through, PPPoE relay
	Mac OS Backup
Features	Enhanced media server (AiPlayer app compatible)
	- Image :
	- Audio : mp3, wma, wav, pcm, mp4, lpcm, ogg
	- Video : asf, avi, divx, mpeg, mpg, ts, vob, wmv, mkv, mov
	AiCloud personal cloud service
	3G/4G data sharing
	Printer Server
	- Multifunctional printer support (Windows only)
	- LPR protocol support
	Download Master
	- Support bt, nzb, http, ed2k
	- Support encryption, DHT, PEX and magnet link
	- Upload and download bandwidth control
	- Download scheduling
	AiDisk file server
	- Samba and FTP server with account management
	Dual WAN
	IPTV support
	Roaming Assist
	OFDMA Reamforming
Dutton	Beamforming Posset Button, Dower Switch, WRS Button, LED Button
Button	Reset Button, Power Switch, WPS Button, LED Button
	Power x 1
	2.4GHz x 1 5GHz-1 x 1
	5GHz-1 x 1 5GHz-2 x 1
LED Indicator	5GHz-2 x 1 WPS x 1
1 6 1 1 2	
	10GE x 1
A STATE OF THE STA	LAN x 1
	WAN x 1
Power Supply	AC Input: 110V~240V(50~60Hz)
	DC Output: 19 V with max. 3.42 A /19.5 V with max. 3.33 A
OS Support -	Windows® 11
	ios
Product Dimensions	354 x 354 x 193 mm (WxDxH)
Product Weight	2180g
Color Box Dimensions	401 x 396 x 141 mm (WxDxH)
Color Box Weight	980g
Total Weight (with Accessory)	3630g *Weight and content may vary by region.
	Wireless router mode
Operation mode	Access point mode
	Repeater mode
	Media bridge mode
	- Constitution of the cons